

USB DATA LOGGERS FOR TEMPERATURE AND HUMIDITY

- Built-in high-precision sensor
- Unit: °C/°F
- Over range indicator
- Low battery display
- Recording status display
- Computer software is included



0333-TH37B

STANDARD DELIVERY

Main unit	1 pc
Software	1 pc
Battery (CR2032)	1 pc

SPECIFICATION

Code	0333-TH37A	0333-TH37B
Parameter	temperature	temperature and humidity
Range	-30°C~70°C/-22°F~158°F	temperature: -30°C~70°C/-22°F~158°F humidity: 0%RH~100%RH
Accuracy	±0.5°C/±0.9°F	temperature: ±0.5°C/±0.9°F humidity: ±3%RH (at 10%RH~90%RH, testing temperature: 25°C), other range ±4%RH
Resolution	0.1°C/0.1°F	temperature: 0.1°C/0.1°F humidity: 0.1%RH
Memory size	30240	17280
Sampling interval	10s	
Logging interval	10s~18h (adjustable)	
Alarm delay	0min~960min (adjustable)	
Alarm type	single, cumulative	
Start delay	0min~254min (adjustable)	
Logging start mode	key operation	
Logging end mode	key operation/Full/insert USB	
Storage temperature	-30°C~70°C	
Power supply	1×3V CR2032 battery	
Dimension (L×W×H)	40×17×95mm	
Net weight	50g	

computer software (included), download data to PC software via USB2.0 port and save the data as XLS/CSV/PDF/PDF/CIN format

