

CALIBRES VERNIER (TIPO SEPARADO)

- Con ajuste fino
- Fabricado en acero inox
- Superficie de lectura cromada satinada



MODELO
POPULAR


Métrico/Pulg.

Graduación 0.02mm/0.001"



(mm)

Código	Rango	Precisión	a	c	d	e	L
1214-300	0-300mm/0-12"	±0.05mm/±0.0020"	10	20	75	10	410
1214-450	0-450mm/0-18"	±0.05mm/±0.0020"	18	24	100	20	620
1214-500	0-500mm/0-20"	±0.05mm/±0.0020"	18	24	100	20	670
1214-600	0-600mm/0-24"	±0.05mm/±0.0020"	18	24	100	20	770
1214-1000	0-1000mm/0-40"	±0.08mm/±0.0030"	24	32	140	20	1216
1214-1500	0-1500mm/0-60"	±0.12mm/±0.0050"	24	42	200	20	1830
1214-2000	0-2000mm/0-80"	±0.14mm/±0.0055"	24	42	200	20	2320

1214-500



tipo separado
(con tornillos)



Métrico

Graduación 0.05mm/1/128"

(mm)

Código	Rango	Precisión	a	c	d	e	L
1214-6004	0-600mm/0-24"	±0.08mm/±0.0030"	18	24	100	20	770
1214-1004	0-1000mm/0-40"	±0.12mm/±0.0050"	24	32	140	20	1216

Pulgadas

Graduación 0.001"

Código	Rango	Precisión	Graduación en escala	a	c	d	e	L
1211-12	0-12"	±0.0020"	pulgadas en la parte inferior y superior	0.394"	0.787"	2.953"	0.500"	16.142"

Pulg./Métrico

Graduación 0.001"/0.02mm

Código	Rango	Precisión	Graduación en escala	a	c	d	e	L
1211-24	0-24"/0-600mm	±0.0020"/±0.05mm	pulgadas en la parte inferior y superior	0.709"	0.945"	3.937"	0.800"	30.315"
1211-40	0-40"/0-1000mm	±0.0031"/±0.08mm	pulgadas en la parte inferior y superior	0.945"	1.26"	5.512"	0.800"	47.874"