

DC RESISTANCE TESTER CODE 9655-RM03

WIRELESS TRANSMISSION
IS OPTIONAL

- Maximum reading: 30000
- Basic accuracy: 0.1%
- Short-circuit zero function
- Temperature compensation function
- Comparator: pass or fail judge



temperature probe (included)

test clip (included)

SPECIFICATION

Function	Range	Resolution	Accuracy of medium speed test	Accuracy of slow speed test	Test current
Resistance test	30mΩ	0.001mΩ	±(0.2%+5d)	±(0.1%+3d)	1A
	300mΩ	0.01mΩ	±(0.2%+3d)	±(0.1%+2d)	1A
	3Ω	0.0001Ω	±(0.2%+3d)	±(0.1%+2d)	100mA
	30Ω	0.001Ω	±(0.2%+3d)	±(0.1%+2d)	10mA
	300Ω	0.01Ω	±(0.2%+3d)	±(0.1%+2d)	1mA
	3kΩ	0.0001kΩ	±(0.2%+3d)	±(0.1%+2d)	1mA
	30kΩ	0.001kΩ	±(0.2%+3d)	±(0.1%+2d)	100μA
Range mode	auto range, manual range and nominal range				
Test speed	slow: 2t/s, medium speed: 12t/s				
Trigger	internal trigger, manual trigger, bus trigger				
Interface	RS232/RS485 communication interface, USB storage interface, temperature compensation interface				
Power supply	AC: 220V±10%, 50Hz/60Hz				
Dimension (L×W×H)	349.5×264×107mm				
Weight	3.5kg				

STANDARD DELIVERY

Main unit	1 pc
RS232 cable	1 pc
Temperature probe	1 pc
Test clip	1 pc

OPTIONAL ACCESSORY

Test probe	9655-TL
Data output cable (keyboard format)	7302-9651
Wireless transmitter (need receiver)	7315-9651

*Receiver code 9651-REC