


## ESC. CON BORDES BISELADOS A 90°



4790-0100



- Cromado satinado
- Cantos biselados para medición interior y exterior
- Fabricado de acero inoxidable endurecido

### DIN875 grado 00

(mm)

Código	Medida (LxW)	Cuadratura		C	D	H
		Interior ( $\alpha$ )	Exterior ( $\beta$ )			
4790-050	50x40mm/2.0x1.6"	2.4 $\mu$ m	2.5 $\mu$ m	13	13	4
4790-075	75x50mm/3.0x2.0"	2.6 $\mu$ m	2.8 $\mu$ m	15	15	4
4790-0100	100x70mm/3.9x2.8"	2.8 $\mu$ m	3.0 $\mu$ m	20	20	5
4790-0150	150x100mm/5.9x3.9"	3.2 $\mu$ m	3.5 $\mu$ m	30	30	6
4790-0200	200x130mm/7.9x5.1"	3.7 $\mu$ m	4.0 $\mu$ m	34	34	7
4790-0300	300x200mm/11.8x7.9"	4.6 $\mu$ m	5.0 $\mu$ m	40	40	8

### DIN875 grado 0

(mm)

Código	Medida (LxW)	Cuadratura		C	D	H
		Interior ( $\alpha$ )	Exterior ( $\beta$ )			
4790-500	50x40mm/2.0x1.6"	6 $\mu$ m	6 $\mu$ m	13	13	4
4790-750	75x50mm/3.0x2.0"	6 $\mu$ m	7 $\mu$ m	15	15	4
4790-1000	100x70mm/3.9x2.8"	7 $\mu$ m	7 $\mu$ m	20	20	5
4790-1500	150x100mm/5.9x3.9"	7 $\mu$ m	8 $\mu$ m	30	30	6
4790-2000	200x130mm/7.9x5.1"	8 $\mu$ m	9 $\mu$ m	34	34	7
4790-3000	300x200mm/11.8x7.9"	10 $\mu$ m	11 $\mu$ m	40	40	8